

Serial No. 09/989,886

- 3 -

#### AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A telecommunications transport network comprising: a plurality of network elements each having a performance monitoring facility operative report overall error rate at the element in each network path using the element, and one or more management systems operative to calculate performance of a segment of a path between two network elements, from the reported overall error rates at the elements, wherein said one or more management systems are operative to subtract a total error rate reported by a first network element from a total error rate reported by a second network element to thereby provide an error rate attributable to particular network domain.

2. (Original) A network as claimed in claim 1, in which a facility is provided to record a maximum error rate, for a given segment of a path for which segment performance is calculated, and including a facility for issuing an alarm if the calculated error rate is closer to the recorded maximum error rate than a predetermined amount.

3. (Cancelled)

4. (Currently Amended) A method of operating a telecommunications transport network comprising a plurality of network elements each having a performance monitoring facility, the method comprising:

reporting overall error rate at the element in a network path using the element, and

calculating performance of a segment of a path between two network elements, from the reported overall error rates at the elements

wherein said step of calculating includes the step of subtracting a total error rate reported by a first network element from a total error rate

Serial No. 09/989,886

- 4 -

reported by a second network element to thereby provide an error rate attributable to particular network domain.

5. (Currently Amended) A method as claimed in claim 34, including recording a maximum error rate, for a given segment of a path for which segment performance is calculated, and issuing an alarm and/or switching the path between the elements, if the calculated error rate is closer to the recorded maximum error rate than a predetermined amount.

6. (Cancelled)

7. (Currently Amended) An apparatus for providing performance monitoring of a telecommunications transport network comprising:

a performance monitoring facility coupled to designated network elements, said performance monitoring facility operative to report overall error rate at the element in each network path using the element, and

one or more management systems operative to calculate performance of a segment of a path between two network elements, from the reported overall error rates at the elements;

wherein said one or more management systems are operative to subtract a total error rate reported by a first network element from a total error rate reported by a second network element to thereby provide an error rate attributable to particular network domain, wherein said management systems include an element management system which couples to a network management system.

8. (Cancelled)

9. (Cancelled)

10. (Currently Amended) The apparatus of claim 87, further including a TCM emulation device coupled to said one or more management systems.